

RILETTO ULTRA-LITE™ (CLEAR)

Riley®

Weighing only 20g, RILETTO ULTRA-LITE™ glasses are ideal for comfortable extended wear. Embossed grip zones on the temple tips help keep the glasses securely in place even in the most arduous of conditions.

SPECIAL FEATURES

- ✓ Extremely lightweight (20g)
- ✓ Ultra slim temples with 'grip zone' tips enhance excellent universal fit even when wearing ear defenders
- ✓ Integrated universal fit moulded nose pad
- ✓ Fits a wide range of face and head shapes
- ✓ Supplied with a microfibre storage pouch



VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	○ RLY00341	2C-1.2 e 1FTKN CE	e EN 166 FT CE	Impacts, UV radiations	TECTON 400® K&N Anti-scratch and Anti-fog / UV400 / Moisture repellent
GREY	● RLY00342	5-2.5 e 1FTKN CE	e EN 166 FT CE	Impacts, UV and Solar radiations	
BLUE	● RLY00343	2-1.4 e 1FTKN CE	e EN 166 FT CE	Impacts, UV radiations	Riley Translucent Mirror Coating. Moisture Repellent + Anti-fog on inside
INDOOR/OUTDOOR	◐ RLY00344	5-1.7 e 1FT CE	e EN 166 FT CE	Impacts, UV radiations	

See overleaf for this product's technical specification →

RILETTO ULTRA-LITE™ (CLEAR)

Riley®

GENERAL SPECIFICATION

LENS BASE	9mm
WEIGHT	20g

PACKAGING

Individually contained in a polythene bag with a Eurosot

PER BOX	10
PER CARTON	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS	Polycarbonate	Dual lens design
NOSE BRIDGE	Polycarbonate	Universal fit, padded
TEMPLE	Polycarbonate	Durable and lightweight
HINGE	Metal	Increased strength


LENS MARKINGS

LENS FILTER TYPE:

2, 2C UV
5 Solar

SCALE NUMBER (SHADE):

1.2 Clear or Amber 1.4 Blue or I/O Waterproof
1.7 Minimises or I/O 2.5 Grey

 Identity of the manufacturer

OPTICAL CLASS:

1 High optical quality

MECHANICAL STRENGTH:

F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
T Protection against high-speed particles at extreme temperatures


PERFORMANCE:

K Resistance to scratches by fine particles

N Resistance to fogging

 Certification mark

FRAME MARKINGS

 Identity of the manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:

F Low energy impact, resists a 6mm, 0.86 g ball at 45 m/s

T Protection against high-speed particles at extreme temperatures

 Certification mark

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PART OF THE GLOBUS GROUP

Based on a substantial heritage of successfully protecting hands, Globus has grown to become one of the world leaders in worker safety, leading the way in technical innovation to provide a range of products that have set the standard for safety, productivity and wearer acceptance.

This focus on creating cutting edge personal protection solutions has now extended to eye and face protection with Riley; a new collection of high performance protective eyewear products engineered with innovation and ingenuity, designed for optimum comfort and styled for safe working.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

www.riley-eyewear.com

E: info@riley-eyewear.com

T: +44 (0)161 877 4747

F: +44(0)161 877 4746

Globus (Shetland) Ltd, 14 Central Park, Mosley Road, Manchester, M17 1NY, UNITED KINGDOM

EC-Type certification issued by:
0194: INSPEC, 56 Leslie Hough Way, Salford, Greater Manchester, M6 6AJ, United Kingdom
The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment.
The manufacturer reserves the right to make any modifications it deems necessary.

© 2018 Globus (Shetland) Ltd | RILEY-DATA-RILETTO-UL-C-0918

**Globus**
GROUP