

REST-KIT2 RESTRAINT KIT



RESTRAINT KIT CONSISTING OF HT2 HARNESS AND RLSC1.5 RESTRAINT LANYARD WITH STEEL CARABINER AND SCAFFOLD HOOK

The Restraint Kit 2 also known as a cherry picker kit consists of our HT2 two point harness, RLSC1.5 restraint lanyard all together in a functionally designed drawstring bag. The HT2 harness has 2 attachment points (Rear and Front) as well as two designated attachment loops for unused lanyards to ensure they aren't connected to harness webbing incorrectly. The RLSC1.5meter rope lanyard comes with a carabiner on one end and scaffold hook on the other to make attaching to an anchoring point quicker and easier. It also has plastic eyelets to reduce wear between the carabiners and rope, increasing product life and ease of use. To be used as restraint lanyard



TECHNICAL INFORMATION

träegatech
PERFORM

ORDER REF. #	HT2
MATERIAL:	POLYESTER, STEEL
SIZES AVAILABLE:	UNIVERSAL
SIZE RANGE:	CHEST: 93 - 115CM LEG: 45 - 108CM
MAX LOAD:	100 kg
PACKING	
PER CASE: 	15 PIECES
PER PACK: 	1 PIECE PER DRAWSTRING BAG

CERTIFICATION BY:

SATRA, SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD. UK.
Notified body: 0321

Tested in accordance with:
EN 361:2002

PRODUCT WEIGHT:	1.2 kg
CARTON: N.W G.W	18.75 kg 19.9 kg



FALL RESTRAINT



FREE-FALL ARREST



DORSAL (REAR) ATTACHMENT



STERNAL (FRONT) ATTACHMENT

If appropriate to the product, EC Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the below web address(s) or by contacting Traega / UCI customer services.

This document and any other statement provided herein by or on behalf of Traega / UCI are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. Traega / UCI assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. Always consult a suitable professional and the enclosed instructions before use.

REST-KIT2/05/18 REV1



»» enhanced performance



Phone: +44 (0)1902 451 451
Email: sales@ultimateindustrial.co.uk
Web: traega.co.uk | ultimateindustrial.co.uk

TECHNICAL INFORMATION



ORDER REF. #	RLSC1.5
MATERIAL:	12mm POLYESTER ROPE
SIZES AVAILABLE:	1 . 5 METER
SIZE RANGE:	CAB1: 16MM SCAF1: 52MM
MAX LOAD:	100 kg
PACKING	
PER CASE: 	30 PIECES
PER PACK: 	1 PIECE PER BAG

CERTIFICATION BY:

SATRA, SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD. UK.
Notified body: 0321

Tested in accordance with:
EN 354:2010

PRODUCT WEIGHT:	900 g
CARTON: N.W G.W	17 kg 18.15 kg

If appropriate to the product, EC Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the below web address(s) or by contacting Traega / UCI customer services.

This document and any other statement provided herein by or on behalf of Traega / UCI are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. Traega / UCI assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. Always consult a suitable professional and the enclosed instructions before use.

