

SCAF-KIT3 SCAFFOLDERS KIT



PREMIUM COMFORT HARNESS KIT WITH EL2 TWIN LEGGED 1.8M ELASTICATED LANYARD WITH QUICK CLIP CONNECTOR

The Scaffolders Kit consists of a HT3B 3point harness with work positioning belt and the WL1 1.8meter webbing lanyard with Shock absorber and scaffold hook, packed in a functionally designed drawstring bag. A best seller for scaffold applications, the 3point harness offers rear and front attachment points with EN358 waistbelt for work positioning. The harness also has two designated attachment loops for unused lanyards to ensure they aren't connected to harness webbing incorrectly. The WL1 is a 1.8meter webbing lanyard with a CAB1 screwgate carabiner to connect to the users EN361 harness and SCAF1 scaffold hook with 52mm opening to attach to the anchoring point



TECHNICAL INFORMATION

träegatech
PERFORM

ORDER REF. #	HT3B
MATERIAL:	POLYESTER, STEEL
SIZES AVAILABLE:	UNIVERSAL
SIZE RANGE:	CHEST: 93 - 113CM LEG: 45 - 108CM
MAX LOAD:	100 kg
PACKING	
PER CASE: 	10 PIECES
PER PACK: 	1 PIECE PER DRAWSTRING BAG

CERTIFICATION BY:

SATRA, SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD. UK.
Notified body: 0321

Tested in accordance with:
EN 361:2002, EN 358:1999

PRODUCT WEIGHT:	1.7 kg
CARTON: N.W G.W	17.5 kg 18.5 kg



If appropriate to the product, EC Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the below web address(s) or by contacting Traega / UCI customer services.

This document and any other statement provided herein by or on behalf of Traega / UCI are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. Traega / UCI assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. Always consult a suitable professional and the enclosed instructions before use.

SCAF-KIT3/05/18 REV1



»» enhanced performance



Phone: +44 (0)1902 451 451
Email: sales@ultimateindustrial.co.uk
Web: traega.co.uk | ultimateindustrial.co.uk

TECHNICAL INFORMATION



ORDER REF. #	WL1
MATERIAL:	30mm polyester. Shock Absorber 45mm
SIZES AVAILABLE:	1.8 meter
SIZE RANGE:	CAB1 - 16mm SCAF1 - 52mm
MAX LOAD:	100 kg
PACKING	
PER CASE: 	15 PIECES
PER PACK: 	1 PIECE PER BAG

CERTIFICATION BY:

SATRA, SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD. UK.
Notified body: 0321

Tested in accordance with:
EN 355:2002 / VG11 RFU SHEET 63

PRODUCT WEIGHT:	1.1kg
CARTON: N.W G.W	9 kg 11 kg

If appropriate to the product, EC Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the below web address(s) or by contacting Traega / UCI customer services.

This document and any other statement provided herein by or on behalf of Traega / UCI are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. Traega / UCI assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. Always consult a suitable professional and the enclosed instructions before use.

