



TECHNICAL DATASHEET

## RLSC<sub>1.5</sub>

## LANYARD WITH CARABINER & HOOK

## 1.5 METER LANYARD WITH STEEL CARABINER AND SCAFFOLD HOOK.

1.5 meters rope lanyard with steel carabiner and Scaffold hook. Made from 12mm polyester rope. Plastic Eyelets to reduce wear between the carabiners and rope increasing product life and ease of use. To be used as restraint lanyard - preventing the wearer from reaching a point where a fall could occur.



## **TECHNICAL INFORMATION**

**träegå**tech

ORDER REF. #	RLSC1.5		CERTIFICATION BY:		
MATERIAL:	12mm POLYESTER ROPE		SATRA, SATRA Technology Centre, Wy Kettering, Northamptonshire, NN16 8SI		
SIZES AVAILABLE:			Notified body: 0321		
CONNECTOR OPENING:	CAB1: 16MM	SCAF1: 52MM	Tested in accordance with: EN 354:2010		
MAX LOAD:	100 Kg		EI4 334.2010		
PACKING					
PER CASE:	20 PIECES		PRODUCT WEIGHT:	900 g	
PER PACK: [M]	1 PIECE PER BAG		CARTON: N.W   G.W	17 kg	

yndham Way, Telford Way, SD. UK.

PRODUCT WEIGHT:	900 g			
CARTON: N.W   G.W	17 kg	1	18.15 kg	



If appropriate to the product, EC Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the below web address(s) or by contacting Traega / UCi customer services

This document and any other statement provided herein by or on behalf of Traega / UCi are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. Traega / UCI assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. Always consult a suitable professional and the enclosed instructions before use.

enhanced **performance** 



Phone: +44 (0)1902 451 451

Email: sales@ultimateindustrial.co.uk

Web: traega.co.uk | ultimateindustrial.co.uk

