

CUT PROTECTION COMBINED WITH LONG LASTING OIL RESISTANT GRIP

A durable double-dipped nitrile coated glove that provides resistance to oil whilst protecting from cuts and lacerations. Ideal for the secure handling of oily components and materials that present a high degree of mechanical risk.

FEATURES

- > Cut resistant: Level D (EN388:2016)
- ¾ coated nitrile with an additional coating of foam nitrile on the palm and fingertips
- > Seamless 13 gauge Hagane Coil® knitted liner
- > Protects from oils, grease and abrasion
- Long lasting grip performance in wet and oily conditions
- Manufactured using an ergonomically designed hand mould that replicates the natural curvature of the human hand
- Wrist protection













SUITABLE FOR

Typical Industries

- Aerospace
- Automotive
- Construction
- Glass
- Steel and Metals

Suitable Applications

- Handling Oily Components with Sharp Edges
- Metal Stamping
- Steel Fixing

CERTIFICATION

CE

CAT II



EN 388:2016

4X41D

See overleaf for explanation







⊔⊢. S-TEX 376

PRODUCT INFORMATION

MATERIALS	LINER:	13 gauge Hagane Coil® (Stainless steel/polyester)	
	COATING:	Foam nitrile over nitrile	
COLOUR	Grey/blue and black		
LENGTH (mm)	250 (size dependent)		
CUFF STYLE	Elasticated knit wrist		

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/S 7/M 8/L 9/XL 10/XXL	SHOS3761 SHOS3762 SHOS3763 SHOS3764 SHOS3765	10 pairs per bag 120 pairs per case


RECOMMENDATIONS FOR USE

- USE: Cut resistant glove. Not suitable for thermal, electrical and Chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

E: sales@globus.co.uk T: +44 (0)161 877 4747 F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com T: +971 4 882 9962 F: +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2020 Globus (Shetland) Ltd | SHO-DATA-S-TEC 376_0620_1