

**SINGLE USE GLOVE, 100% NITRILE, POWDER FREE, 280MM LONG, 0.10MM THICK**

High performance, powder-free, extended cuff nitrile single use examination glove. Significantly stronger alternative to latex, dual certified (Industrial and Medical) and food safe.

**FEATURES**

- › High quality nitrile, soft and durable
- › Palm thickness 0.10mm (4 mil), weight: 6.5g size M
- › High resistance to penetration and projections of many chemicals
- › Textured finish on fingertips for improved grip and touch
- › Extended cuff (280mm length)
- › Powder-free, latex free, non-sterile, AQL 1.5 Chlorinated inside to offer more comfort and reduce friction when donning
- › Antistatic properties due to inherent antistatic properties of nitrile
- › Approved for food handling
- › Dual labelling: PPE and medical
- › Medical device compliant (MDD 93/42/EEC), conforms to EN455 (all parts)
- › Tested against chemotherapy drugs according to ASTM D6978-05
- › Compliant with ASTM D6319-2019 and ASTM D5151-2019



**SUITABLE FOR**

**Typical Industries**

- Aerospace
- Chemical
- Electronics
- Food
- Pharmaceutical
- Manufacturing
- Oil and Gas

**Suitable Applications**

- Chemical Handling
- Food Handling
- Handling Oily Components
- Laboratory Analysis
- Light Assembly
- Paint Spraying
- Examination

**CERTIFICATION**

CAT III	EN ISO 374-1:2016/Type B	EN ISO 374-5:2016		EN455
2777	KPT	Virus		MEDICAL DEVICE

See overleaf for explanation

**PRODUCT INFORMATION**

<b>MATERIALS</b>	LINER:	Nitrile
	COATING:	N/A
<b>COLOUR</b>	Blue	
<b>LENGTH (mm)</b>	280	
<b>CUFF STYLE</b>	Beaded	

**ORDERING DETAILS**

SIZE	CODE	PACKAGING
6/XS	SKG00428DB	100 singles per box (90 singles on size XXL)
7/S	SKG00428DD	
8/M	SKG00428DF	
9/L	SKG00428DH	
10/XL	SKG00428DJ	
11/XXL	SKG00428DL	10 boxes per case

**RECOMMENDATIONS FOR USE**

- **USE:** Single use glove. Not suitable for mechanical, thermal, heat, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

**CERTIFICATION LEGENDS**



**RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016**

CODE	CHEMICAL	CODE	CHEMICAL	TYPE OF GLOVES	BREAKTHROUGH TIME
A	Methanol	J	n-Heptane	A	≥30 min for at least 6 chemicals
B	Acetone	K	Sodium hydroxide 40%		
C	Acetonitrile	L	Sulphuric acid 96%		
D	Dichloromethane	M	65% Nitric acid	B	≥30 min for at least 3 chemicals
E	Carbon Disulfide	N	99% Acetic acid		
F	Toluene	O	25% Ammonium hydroxide	C	≥10 min for at least 1 chemical
G	Diethylamine	P	30% Hydrogen peroxide		
H	Tetrahydrofurane	S	40% Hydrofluoric acid		
I	Ethyl acetate	T	37% Formaldehyde		

EN455-1:	Freedom from holes
EN455-2:	Physical properties
EN455-3:	Biological evaluation
EN455-4:	Shelf Life



**PROTECTION AGAINST MICRO-ORGANISMS EN 374-5**  
 VIRUS = Glove has passed ISO 16604:2004 (method B)



**FOOD CONTACT DIRECTIVE EC 10/2011**

**EUROPE**

[www.globusgroup.com](http://www.globusgroup.com)

**E:** sales@globus.co.uk  
**T:** +44 (0)161 877 4747  
**F:** +44 (0)161 877 4746

**MIDDLE EAST AND AFRICA**

[www.globusgroup.com/gcc](http://www.globusgroup.com/gcc)

**E:** gcc@globusgroup.com  
**T:** +971 4 882 9962  
**F:** +971 4 882 9963

