

**ANTI-STATIC, SINGLE- USE GLOVE, 100% NITRILE, POWDER- FREE, SILICONE-FREE, 300MM LONG, 0.16MM THICK**

Premium performance, powder-free, extended cuff, nitrile, single-use glove with anti-static properties (ESD). Extremely strong and high resistance to chemicals.

**FEATURES**

- › High-quality nitrile, soft and durable
- › Palm thickness 0.16mm (6 mil), weight: 9.1g, size M
- › High resistance to penetration and projections of many chemicals
- › Extended cuff (300mm length) to protect the forearm
- › Textured finish on fingertips to enhance grip
- › Powder-free, latex-free, non-sterile, AQL 1.5
- › Double Chlorinated inside and outside to offer increased comfort, low tack and reduce friction when donning
- › Anti-static properties according to EN 16350:2014: vertical resistance  $14.5 \times 10^6 \Omega$
- › Eliminates static charge build-up to help prevent sparks and flare-ups in flammable environment
- › Silicone-free



**SUITABLE FOR**

**Typical Industries**

- Chemicals
- Electronics
- Manufacturing
- Oil and Gas
- Pharmaceutical
- Repair and Finishing

**Suitable Applications**

- Chemical Handling
- Handling Oily Components
- Laboratory Analysis
- Light Assembly
- Paint Spraying

**CERTIFICATION**

CAT III	EN ISO 374-1:2016/Type B	EN ISO 374-5:2016	EN 16350:2014
0598	JKPT		

See overleaf for explanation

## PRODUCT INFORMATION

MATERIALS	LINER:	Nitrile
	COATING:	N/A
COLOUR	Black	
LENGTH (mm)	300 mm	
CUFF STYLE	Beaded	

## ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS	SKG00630BB	100 singles per box
7/S	SKG00630BD	
8/M	SKG00630BF	10 boxes per case
9/L	SKG00630BH	
10/XL	SKG00630BJ	
11/XXL	SKG00630BL	

## RECOMMENDATIONS FOR USE

- **USE:** Single use glove. Not suitable for Mechanical, thermal, heat, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement.
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight.
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use.

## CERTIFICATION LEGENDS



### RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL	TYPE OF GLOVES	BREAKTHROUGH TIME
A	Methanol	J	n-Heptane	A	≥30 min for at least 6 chemicals
B	Acetone	K	Sodium hydroxide 40%		
C	Acetonitrile	L	Sulphuric acid 96%	B	≥30 min for at least 3 chemicals
D	Dichloromethane	M	65% Nitric acid		
E	Carbon Disulfide	N	99% Acetic acid	C	≥10 min for at least 1 chemical
F	Toluene	O	25% Ammonium hydroxide		
G	Diethylamine	P	30% Hydrogen peroxide		
H	Tetrahydrofurane	S	40% Hydrofluoric acid		
I	Ethyl acetate	T	37% Formaldehyde		



### EN16350:2014 ELECTROSTATIC PROPERTIES



### PROTECTION AGAINST MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604:2004 (method B)

### EUROPE

[www.globusgroup.com](http://www.globusgroup.com)

**E:** [sales@globus.co.uk](mailto:sales@globus.co.uk)  
**T:** +44 (0)161 877 4747  
**F:** +44 (0)161 877 4746

### MIDDLE EAST AND AFRICA

[www.globusgroup.com/gcc](http://www.globusgroup.com/gcc)

**E:** [gcc@globusgroup.com](mailto:gcc@globusgroup.com)  
**T:** +971 4 882 9962  
**F:** +971 4 882 9963

