



CUT RESISTANT GLOVE WITH REINFORCED SPONGE NITRILE PALM

A durable, lightweight glove providing maximum resistance to cuts and protection when handling sharp, slippery objects such as glass and metal.

FEATURES

- > Cut resistant: Level B (EN 388:2016)
- > Excellent grip in damp, oily and dry conditions
- > High levels of flexibility and dexterity
- > Advanced sponge nitrile coating
- Lightweight 13 gauge liner and enhanced protective padding
- > Reinforced thumb-line enhances durability
- Breathable liner keeps hand cool and helps to reduce perspiration
- > Elasticated wrist provides a secure fit
- > Seamless liner prevents irritation









SUITABLE FOR

Typical Industries

- Automotive
- Construction
- Engineering
- Glass
- Manufacturing
- Metal
- Transport

Suitable Applications

- Bottling/Canning
- Metal Fabrication
- Scaffolding

CERTIFICATION



See overleaf for explanation







SKYTEC ULTIMUS LITE™

PRODUCT INFORMATION

| MATERIALS | LINER: | 13 gauge HPPE, glass fibre, nylon |
|-------------|------------------------|-----------------------------------|
| | COATING: | Nitrile Sponge |
| COLOUR | Black/Light Grey | |
| LENGTH (mm) | 250 (size dependent) | |
| CUFF STYLE | Elasticated knit wrist | |

ORDERING DETAILS

| SIZE | CODE | PACKAGING |
|----------------------------|--------------------------------------|--|
| 7/S 8/M 9/L 10/XL | SKY681 SKY682 SKY683 SKY684 | 10 pairs per bag 120 pairs per case |


RECOMMENDATIONS FOR USE

- USE: General handling glove with cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement $% \label{eq:continuous} % \label{eq:continuo$
- STORAGE: Store in dry conditions in the original packaging and away from
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

E: sales@globus.co.uk +44 (0)161 877 4747 +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com +971 4 882 9962 F: +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2021 Globus (Shetland) Ltd | SKY-DATA-ULTIMUS LITE-0420 1