Benchmark **>** BM08



Lightweight wrap-around style safety spectacle.



VERSIONS		REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	0	RLYB0021	2C-1.2 @ 1FT C €	€ EN 166 FT C €	Impacts, UV radiations	Anti-scratch
GREY		RLYB0022	5-2.5 € 1FT C €	€ EN 166 FT C €	Impacts, UV and Sun glare	
CLEAR	0	RLYB0024	2C-1.2 € 1FT C €	€ EN 166 FT C €	Impacts, UV radiations	Anti-scratch and Anti-fog
DK GREY		RLYB0026	5-3.1 € 1FT C €	€ EN 166 FT C €	Impacts, UV and Sun glare	



Benchmark **>** BM08



GENERAL SPECIFICATIONS

LENS BASE	10mm
WEIGHT	28g

PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS AND NOSEBRIDGE	Polycarbonate	Single piece, moulded with side protection
TEMPLE	Polycarbonate	Robust and durable
HINGE	Stainless steel	Hard wearing

LENS MARKINGS

LENS FILTER TYPE:

2C UV

5 Solar

SCALE NUMBER (SHADE):

1.2 Clear

2.5 Grey

3.1 Dark Grey

Identity of the manufacturer

OPTICAL CLASS:

1 High optical quality

MECHANICAL STRENGTH:

- **F** Low energy impact, resists a 6mm, 0.86g ball at 45m/s
- T Protection against high-speed particles at extreme temperatures
- C€ Certification mark

FRAME MARKINGS

 ${\cal C}$ Identity of the manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:

- F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
- **T** Protection against high-speed particles at extreme temperatures
- **C** Certification mark

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is

damaged also replace the complete product. After each use it is recommended to keep the spectacles or

goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

